Think GAIA
For Life and the Earth

SANYO

Ultra-Low Temperature V.I.P.™ Freezer

MDF-U73V

Temperature
(Ambient temp. 30°C)
-86°C

Effective capacity
728Liter/25.7cu.ft.

Patented V.I.P.™
(Vacuum Insulation Panel)

Extra-large capacity, space saving Ultra-Low Freezer with Improved energy consumption

- V.I.P.™ technology maximises storage capacity
- Safe operation with Status Alert continuous condition monitoring
- The inner doors are removable for cleaning and defrosting
- Enhanced security
- Improved accessibility
- Quiet operation
- Improved energy consumption
- Can hold up to 528 pcs of 2-inch boxes or 336 pcs of 3-inch boxes

MDF-U73V

VIP series
Vacuum Insulation Panel

MDF-U73V

Features

EVOLUTIONARY DESIGN

- SANYO V.I.P.™ Evolution Series -86˚C ultra-low temperature freezers use patented revolutionary vacuum insulation cabinet construction that reduces the wall thickness from 14cm to 7cm (5.5" to 2.7") and achieves up to 30% more storage capacity than a conventionally insulated freezer without increasing the footprint.
- The newly developed refrigeration system and the freezer structure offer a quiet experimental environment.
- Achieves 10% higher energy conservation than previous model. (For model rated 220V, 50Hz)
- The newly developed back cover combined with new aerodynamically designed and placed components in the refrigeration compartment provide superior air flow, making it possible to drastically reduce the stress on the freezer and contributing to excellent durability.



- Two independent and insulated inner doors with gaskets prevent cold air leakage.

RELIABILITY

- Status Alert (Condition monitor) Monitors ambient and system conditions continuously and notifies of any abnormalities before a problem happens.

ACCESSIBILITY

- A beak style inner door latch tightly closes the inner door against the freezer frame. It also helps make opening and closing the door smoother.
- The condenser filter is situated at the bottom right side of the front panel to make filter removal and cleaning easier.

SAFETY

- Alarm lamp and buzzer offer secure warning of power failure or abnormal temperature increase.
- High and low temperature warning provides an audible and visual alarm when the temperature deviates more than ±5˚C to ±20˚C (adjustable) from the set point.
- Alarm ring-back function ensures that buzzer will resume operation, should alarm conditions continue after it is silenced.
- Microprocessor-controlled filter-clog check function protects the refrigeration circuit.
- The rugged, one-handed outer door latch has a hole to allow a padlock to securely protect valuable samples.

- Control panel with digital display for easy operation.

Specifications

Model	MDF-U73V
Temperature range	–50˚C to –86˚C (1˚C increments)
Maximum cooling performance	–86˚C (Ambient temp. 30˚C)
Exterior dimensions (W x D x H)	1010 x 875 x 2010mm (39.8" x 34.4" x 79.1")
Interior dimensions (W x D x H)	870 x 600 x 1400mm (34.2" x 23.6" x 55.1")
Net weight	Approx. 350kg (772 lbs.)
Effective capacity	728 L (25.7 cu.ft.)
Shelves	Stainless steel, 3 shelves
Access port	17mm diameter, 3 locations (back, bottom left/right corner)
Compressor	Hermetic type, Output: 1100 W (high stage side), 1100 W (low stage side)
Refrigerant	HFC
Alarm	High/low temperature, Power failure, Filter check, Self diagnostics, Door check, Part replacement nortification
Remote alarm contact	Allowable contact capacity: DC 30V, 2A
Accessories	1 set of keys, 1 scraper

*Cooling performance is indicated by the temperature reached at the center of the freezer (at ambient temperature of 30°C with no load). In order to use the freezer at a stable temperature for a long time, it is recommended that the temperature be set to at least 5°C higher than the indicated lowest temperature.
In addition, depending on the usage conditions, it may not be possible to reach the indicated lowest temperature.

Caution:
SANYO guarantees the product under certain warranty conditions. SANYO in no way shall be responsible for any loss of content or damage to content.

• Appearance and specifications are subject to change without notice.

Performance Data

Pull-down characteristics



Pull-up characteristics during power failure



CO_2 backup system operation characteristics



Dimensions

[Unit : mm (inch)]



Options

Inventory rack
IR-220U
IR-224U

Circular recorder
MTR-G85

Strip chart recorder
MTR-85H

Recorder mounting bracket
MDF-S3085
(for MTR-85H)

LCO_2 backup system
CVK-UB2
LN_2 backup system
CVK-UBN2

SANYO DAQ (data acquisition) System
MTR-5000/ Ethernet (LAN) Interface **MTR-L03**
or RS232C/RS485 Interface **MTR-480**

SANYO Electric Co., Ltd., Biomedical Division, Gunma is certified for:
Quality management system: ISO9001 / Medical devices quality management system: ISO13485 / Environmental management system: ISO14001

Distributed by:

SANYO Electric Co., Ltd.
Biomedical Division
http://biomedical.sanyo.com/

©2009 SANYO Printed in Japan 2009.9 MA
SHR148